

# EDM35-0VF0A024A

EDS/EDM35

MOTOR FEEDBACK SYSTEMS

**SICK**  
Sensor Intelligence.



Illustration may differ



## Ordering information

| Type            | Part no. |
|-----------------|----------|
| EDM35-0VF0A024A | 1106846  |

Other models and accessories → [www.sick.com/EDS\\_EDM35](http://www.sick.com/EDS_EDM35)

## Detailed technical data

### Safety-related parameters

|  |  |
|--|--|
| <b>MTTF<sub>D</sub> (mean time to dangerous failure)</b> | 150 years (EN ISO 13849) <sup>1)</sup> |
|--|--|

<sup>1)</sup> This product is a standard product and does not constitute a safety component as defined in the Machinery Directive. Calculation based on nominal load of components, average ambient temperature 60 °C, frequency of use 8760 h/a. All electronic failures are considered hazardous. For more information, see document no. 8015532.

### Performance

| Position   |                      |
|--|----------------------|
| Resolution per revolution                        | 24 bit               |
| System accuracy                                  | ± 25 " <sup>1)</sup> |
| Signal noise (σ)                                 | ± 1 " <sup>2)</sup>  |
| Number of the absolute ascertainable revolutions | 4,096                |
| Available memory area                            | 8,192 Byte           |

<sup>1)</sup> In accordance with DIN ISO 1319-1, position of the upper and lower error limit depends on the installation situation, specified value refers to a symmetrical position, i.e. deviation in upper and lower direction is the same.

<sup>2)</sup> Repeatability standard deviation in accordance with DIN 1319-1:1995.

### Interfaces

|  |   |
|--|---|
| <b>Code sequence</b>                               | Increasing, when turning the shaft For clockwise rotation, looking in direction "A" (see dimensional drawing) |
| <b>Communication interface</b>                     | HIPERFACE DSL <sup>®</sup>  |
| <b>Initialization time</b>                         | ≤ 500 ms <sup>1)</sup>  |
| <b>Measurement external temperature resistance</b> | 32-bit value, without prefix (1 Ω) 0 ... 209.600 Ω <sup>2)</sup>  |

<sup>1)</sup> From reaching a permitted operating voltage.

<sup>2)</sup> Without sensor tolerance; at -40 °C ... +160 °C: NTC +2K; PTC+3K (KTY84-130/PT1000). For additional conversion function of PT1000 to KTY84/130, see technical description.

### Electrical data

|                                  |                           |
|----------------------------------|---------------------------|
| <b>Connection type</b>           | Male connector, 8-pin     |
| <b>Supply voltage</b>            | 7 V ... 12 V              |
| <b>Warm-up time voltage ramp</b> | Max. 180 ms <sup>1)</sup> |

<sup>1)</sup> Duration of voltage ramp between 0 and 7.0 V.

<sup>2)</sup> Current rating applies when using interface circuit suggestions as shown in HIPERFACE DSL<sup>®</sup> manual (8017595).

|                              |                        |
|------------------------------|------------------------|
| <b>Current consumption</b>   | ≤ 150 mA <sup>2)</sup> |
| <b>Compatible with sHub®</b> | ✓                      |

<sup>1)</sup> Duration of voltage ramp between 0 and 7.0 V.

<sup>2)</sup> Current rating applies when using interface circuit suggestions as shown in HIPERFACE DSL® manual (8017595).

## Mechanical data

|                                       |  |
|---------------------------------------|--|
| <b>Shaft version</b>                  | Tapered shaft  |
| <b>Dimensions</b>                     | See dimensional drawing  |
| <b>Weight</b>                         | ≤ 100 g  |
| <b>Moment of inertia of the rotor</b> | 5 gcm <sup>2</sup>   |
| <b>Operating speed</b>                | ≤ 9,000 min <sup>-1</sup>  |
| <b>Angular acceleration</b>           | ≤ 250,000 rad/s <sup>2</sup>   |
| <b>Start up torque</b>                | ≤ 0.6 Ncm, +20 °C  |
| <b>Permissible movement static</b>    | ± 1 mm axial <sup>1)</sup>   |
| <b>Permissible movement dynamic</b>   | ± 0.1 mm radial  |
| <b>Life of ball bearings</b>          | 50,000 h at 6,000 min <sup>-1</sup> (at a flange temperature of 70 °C) |

<sup>1)</sup> Temperature expansion, mechanical attachment.

## Ambient data

|  |   |
|--|---|
| <b>Operating temperature range</b>                 | -40 °C ... +115 °C <sup>1)</sup>  |
| <b>Storage temperature range</b>                   | -40 °C ... +125 °C, without package                                       |
| <b>Relative humidity/condensation</b>              | 90 %, Condensation not permitted  |
| <b>Resistance to shocks</b>                        | 100 g, 6 ms (according to EN 60068-2-27)                                  |
| <b>Frequency range of resistance to vibrations</b> | 50 g, 10 Hz ... 2,000 Hz (EN 60068-2-6)                                   |
| <b>EMC</b>   | According to EN 61000-6-2, EN 61000-6-4 and IEC 61326-3 <sup>2)</sup>     |
| <b>Enclosure rating</b>                            | IP40, When cover is closed and mating connector is attached (IEC 60529-1) |

<sup>1)</sup> Given typical thermal connection between motor flange and encoder stator coupling. The max. internal sensor temperature may not exceed 125 °C.

<sup>2)</sup> According to the listed standards, EMC is guaranteed if the motor feedback system with mating connector inserted is connected to the central grounding point of the motor controller via a cable shield. If other shielding concepts are used, users must perform their own tests. Class A device.


## Classifications

|                     |          |
|---------------------|----------|
| <b>ECLASS 5.0</b>   | 27270590 |
| <b>ECLASS 5.1.4</b> | 27270590 |
| <b>ECLASS 6.0</b>   | 27270590 |
| <b>ECLASS 6.2</b>   | 27270590 |
| <b>ECLASS 7.0</b>   | 27270590 |
| <b>ECLASS 8.0</b>   | 27270590 |
| <b>ECLASS 8.1</b>   | 27270590 |
| <b>ECLASS 9.0</b>   | 27270590 |
| <b>ECLASS 10.0</b>  | 27273805 |
| <b>ECLASS 11.0</b>  | 27273901 |
| <b>ECLASS 12.0</b>  | 27273901 |
| <b>ETIM 5.0</b>     | EC001486 |



## PIN assignment

Supply/Communication pin assignment




V connection type

| PIN | Signal          | Explanation            |
|-----|-----------------|------------------------|
| 1   | +U <sub>S</sub> | Supply                 |
| 2   | GND             | Ground connection      |
| 3   | DSL-            | DSL negative           |
| 4   | DSL+            | DSL positive           |
| 5   | RxD+            | Receiver data positive |
| 6   | RxD-            | Receiver data negative |
| 7   | TxD-            | Sender data negative   |
| 8   | TxD+            | Sender data positive   |

Recommended mating connector: JST (GHR-08V-S)

## Diagrams

Typical inrush current (A)



### Recommended accessories

Other models and accessories → [www.sick.com/EDS\\_EDM35](http://www.sick.com/EDS_EDM35)

| Brief description       | Type            | Part no. |
|-------------------------|-----------------|----------|
| Spare parts             |                 |          |
| EDM35 cover set, 10 pcs | BEF-CAP-EDM-010 | 2139997  |
| EDM35 cover set, 40 pcs | BEF-CAP-EDM-040 | 2139999  |

## SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is “Sensor Intelligence.”

## WORLDWIDE PRESENCE:

Contacts and other locations –[www.sick.com](http://www.sick.com)