CUI INC
a bel group



# SERIES: VSUU-120C | DESCRIPTION: AC-DC POWER SUPPLY

## FEATURES

- universal input (90 ~ 264 Vac)
- up to 120 W continuous power
- active power factor correction
- IEC/EN/UL 62368 certified
- over voltage, over current, short circuit protection




## MODEL

| MODEL | output voltage[1] (Vdc) | output current max (A) | output power max (W) | ripple and noise max (mVp-p) | efficiency typ (%) |
|---|---|---|---|---|---|
| VSUU-120C-9 | 9 | 13.33 | 120 | 100 | 75 |
| VSUU-120C-12 | 12 | 10.0 | 120 | 130 | 75 |
| VSUU-120C-15 | 15 | 8.0 | 120 | 150 | 78 |
| VSUU-120C-24 | 24 | 5.0 | 120 | 200 | 82 |

Note: 1. Factory adjustable.

## PART NUMBER KEY



## INPUT

| parameter | conditions/description | min | typ | max | units |
|---|---|---|---|---|---|
| voltage | | 90 | | 264 | Vac |
| frequency | | 47 | | 63 | Hz |
| current | at 100 Vac, full load<br>at 240 Vac, full load | | | 1.75<br>0.72 | A<br>A |
| inrush current | at 100 Vac, 25°C, full load, cold start<br>at 240 Vac, 25°C, full load, cold start | | | 37<br>88 | A<br>A |
| power factor | full load at 240 Vac | 0.95 | | 1.0 | |

## OUTPUT

| parameter | conditions/description | min | typ | max | units |
|---|---|---|---|---|---|
| line regulation | full load at 100 ~ 120 Vac | | | 1 | % |
| load regulation | at 230 Vac, 10 ~ 90% load | | | 5 | % |
| temperature coefficient | all output models, 100 ~ 240 Vac | | | ± 0.04 | %/°C |
| transient response | full load to half load at 110 Vac | | | 4 | ms |
| start-up | full load at 100 ~ 240 Vac | | | 3 | s |
| hold-up | full load at 100 Vac | 16 | | | ms |

## PROTECTIONS

| parameter | conditions/description | min | typ | max | units |
|---|---|---|---|---|---|
| over voltage protection | | 112 | | 132 | % |
| over current protection | | 110 | | 150 | % |
| short circuit protection | auto recovery | | | | |

## SAFETY & COMPLIANCE


| parameter | conditions/description | min | typ | max | units |
|---|---|---|---|---|---|
| isolation voltage | input to output<br>input to earth ground | 4,242<br>2,121 | | | Vdc<br>Vdc |
| safety approvals | certified to 62368: IEC/EN/UL<br>UKCA | | | | |
| EMI/EMC | CISPR-32/EN 55032:2012/AC:2013 Class B<br>EN 61000-3-2:2014<br>EN 61000-3-3:2013 | | | | |
| leakage current | full load at 240 Vac | | | 0.75 | mA |
| RoHS compliant | yes | | | | |

## ENVIRONMENTAL


| parameter | conditions/description | min | typ | max | units |
|---|---|---|---|---|---|
| operating temperature | see derating curve | 0 | | 70 | °C |
| storage temperature | | -40 | | 85 | °C |
| operating humidity | non-condensing | 0 | | 95 | % |
| storage humidity | | 0 | | 95 | % |

## DERATING CURVES

***INPUT VOLTAGE DERATING CURVE***





***TEMPERATURE DERATING CURVE***




## MECHANICAL DRAWING

units: mm[inches]
tolerance: ±0.5mm

| PIN | Function |
|---|---|
| 1 | OUT |
| 2 | OUT |
| 3 | OUT |
| 4 | OUT |
| 5 | OUT |
| 6 | OUT |
| 7 | RTN |
| 8 | RTN |
| 9 | RTN |
| 10 | RTN |
| 11 | RTN |
| 12 | RTN |
| 13 | no connect |




Note:
1. Input connector mates with Molex housing 09-52-4054 and Molex 2478 series crimp terminal.
2. Output connector mates with Molex housing 09-52-4134 and Molex 2478 series crimp terminal.

## REVISION HISTORY

| rev. | description | date |
|---|---|---|
| 1.0 | initial release | 12/14/2020 |
| 1.01 | mechanical drawing updated | 04/20/2021 |
| 1.02 | mechanical drawing updated | 08/27/2021 |
| 1.03 | derating curves updated | 02/02/2022 |
| 1.04 | UKCA added to specification | 02/24/2022 |

The revision history provided is for informational purposes only and is believed to be accurate.

CUI INC
a bel group

**Headquarters**
20050 SW 112th Ave.
Tualatin, OR 97062
**800.275.4899**

Fax 503.612.2383
**cui**.com
techsupport@cui.com

CUI offers a two (2) year limited warranty. Complete warranty information is listed on our website.

CUI reserves the right to make changes to the product at any time without notice. Information provided by CUI is believed to be accurate and reliable. However, no responsibility is assumed by CUI for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

CUI products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.